

---

# PH 80 PORTABLE LAMP

Designed by Poul Henningsen

---



---

## Technical specifications

### Materials

Shades: Injection molded PC.  
Top, cone, heat sink, stem top, base: Die-casted aluminum.  
Stem: Extruded aluminum.  
Diffuser: Injection molded clear PC.

### Information

Please note that the PH 80 Portable Lamp comes with a USB-cable but without an adapter. For the E-socket product variants, bulbs are not included. LED light source is part of the product.

### Finishes

White opal shades.  
Red or white cone.  
Socket house in white or high lustre chrome plated.  
Stem top in white or black.  
Stem in white or high lustre chrome plated.  
Base in black or white.

### Mounting

Cord: 1.5 m. USB-C/USB-C. (Not included)  
Light control: Switch on base.  
White light indicator on base when charging.  
Batteries: 2 x LiPo, rechargeable, replaceable.  
Battery lifetime: 5 hours at 100%.  
Step- and stepless-dim, and customer user setting. For mounting instructions, see download section on the product detail page.

---

## Variant Options

For particular variant options, please check our online Product Variants Configurator on the

---

# PH 80 PORTABLE LAMP

Designed by Poul Henningsen

---

product detail page.

VARIANT NO.	LIGHT SOURCE	VOLTAGE/FRQ	LUMEN	FEATURES	CABLE
5744172325	LED 3000-1800K D2W 4W	5V, 2A/10W	174	-	Without cord
5744172338	LED 3000-1800K D2W 4W	5V, 2A/10W	174	-	Without cord

---

## Variants

VARIANT NUMBER	COLOR, RAL	W / H / L (IN) / W (LB)
5744172325	OPAL WHITE/HIGH LUSTRE CHROME PLATED	230 / 305 / 230 IN / 0.8 LB
5744172338	OPAL WHITE/WHITE	230 / 305 / 230 IN / 0.8 LB