

TOLDBOD 6.1 WALL

The light is directed 100% downwards and the shade has a matte white painted interior emitting a soft, diffused, comfortable light.



**Hareskov Kirkes
Menighedshus**



Skagen

Product info

Environmental Product Specification

This product is compliant with the requirements contained in the European Directives, RoHS Directive 2011/65 and 2015/863. This product is designed so that 100% of the product can be disassembled and reused.

Information

Electrical: System Wattage: 10 W Delivered lumens: 189 lm Efficacy: 18.9 lm/W Certifications: cULus, Wet Location Protection class IP44 IK class 05 BUG Rating: B1-U2-G1 Controllability: Phase dimming Min.-Max. Ambient Temp: -20°C to +40°C Actual performance dependent upon screw-base lamp used.

Mounting

Surface: Mounted directly to finished surface over a recessed 4" octagonal junction box.

Finish

Black or natural painted aluminum, powder coated.

Materials

Shield: Tempered sand blasted glass. Wall plate: Die cast aluminum. Luminaire head: Die cast aluminum. Arm: Extruded aluminum.

Sizes and weight

Width x Height x Length (in.) | 6.1 x 6.2 x 10.5 Max 2.6 lbs

Compliance

cULus, Wet location.

Light source

1x10W G16.5/IF Candelabra US

Information

Electrical:

System Wattage: 10 W

Delivered lumens: 189 lm

Efficacy: 18.9 lm/W

Certifications:

cULus, Wet Location

Protection class IP44

IK class 05

BUG Rating: B1-U2-G1

Controllability: Phase dimming

Min.-Max. Ambient Temp: -20°C to +40°C


Actual performance dependent upon screw-base lamp used.




Related products



Toldbod 11.4 Post



Toldbod Pendant

Toldbod 6.1/8.7 Glass
Pendant

Product variants

Color	Light source	Voltage frequency
Toldbod 6.1 Bollard <input checked="" type="radio"/> Black texture	1x10W G16.5/IF Candelabra US	120V
<input type="radio"/> Natural paint aluminum		

Product description

Small Scale wall fixture with a nautical shape and form—design based on Poul Henningsen's ellipse reflector. Ideal for garden and residential applications. The Toldbod Wall is part of a product family which includes a post top, bollard and pendants. Standard exterior colors are black or natural aluminum paint colors; additional colors are available.

Mounting

Surface: Anchored directly to the wall, centered over junction box. Three mounting holes 0.37 IN diameter on bolt circle 5.2 IN diameter at 120°. Mounting hardware by others.

Light description

The light is directed 100% downwards and the shade has a matte white painted interior emitting a soft, diffused, comfortable light from a candelabra screw-base lamp (by others). The clear polycarbonate lens extends below the housing, creating a horizontal edge-lit accent. Features pleasant lighting comfort.

Design

Louis Poulsen A/S

Material

Shield: Tempered, sand blasted glass, 0.03" thick. Luminaire head and wall plate: Die cast aluminum, 0.04" thick. Mounting arm: aluminum, 0.03" thick. Standard finish is matte, textured surface powder coat with minimum 2 mils thickness in black or natural painted aluminum.

Weight

Min: 2.635 lbs Max: 2.635 lbs

Other functions

Custom finishes. Custom wall brackets.

Finish

Black texture, Natural paint aluminum

Voltage

120V

Light distribution diagrams

Cartesian|solux|Polar|Bug

□ □ □ □

Spare parts & accessories

Product

Variant number

GRUB SCREW MS M12X12 (3PCS)

5743145887