

VL 45 RADIOHUS PENDANT

The fixture provides uniform, general and diffuse illumination. The opening at the bottom of the glass produces downwards directed light. The quality of the glass ensures that the fixture is evenly lit.



Vilhelm Lauritzen

Vilhelm Lauritzen (1894–1984) is one of the most significant architects in the history of Denmark; he was the trail-blazing figurehead of Danish functionalism. A number of his buildings – Nørrebro Theatre (1931–32), Daells Varehus department store (1928–35), Radiohuset (1936–41) and the first airport built in Kastrup (1937–39) – represented the concentrated essence of contemporary life.



Product info

Information

Electrical: System Wattage: 10W - 44W LED Wattage: 9 W or 42 W Delivered lumens: 440 - 2,711 Efficacy: 44.0 lm/W - 123.2 lm/W Certifications: cULus, Dry Location Protection class IP20 Controllability: 0-10V Dimming (LED variants); Phase dimming (incandescent variants) Color Rendering: Ra \geq 90 for LED variants. Performance dependent upon screw-base lamp used in socketed variants.

Mounting

Canopy: White. Cord type: 2-conductor, 18 AWG white braided fabric covered power cord. Cord length: 12'.

Finish

Glossy opal glass. Brushed brass, untreated.

Materials

Mouth-blown polished opal glass. Untreated brushed brass, will patinate.

Sizes and weight

width x Height x Length (in.) | 9.8 x 12.9 x 9.8 Max 4.5 lbs | 14.6 x 17.6 x 14.6 Max 11.4 lbs | 6.8 x 9.7 x 6.8 Max 3.1 lbs | 6.9 x 9.7 x 6.9 Max 3.1 lbs | 250 x 328 x 250 Max 2.0 lbs | 175 x 246 x 175 Max 1.3 lbs

Compliance

cULus, Damp location.

Specification notes

a. 6.9 IN available only in 10W/G16.5/candelabra. b. 9.8 IN available only in 22W/A-21/medium. c. 14.6 IN available in 22W/A-21/medium or 44W/LED. d. Incandescent variants available only in 120V. e. LED variants available with mains dimming at 120V or 0-10V dimming with 120-277V.

Information

Electrical:

System Wattage: 10W - 44W

LED Wattage: 9 W or 42 W

Delivered lumens: 440 - 2,711

Efficacy: 44.0 lm/W - 123.2 lm/W

Certifications:

cULus, Dry Location

Protection class IP20

Controllability: 0-10V Dimming (LED variants); Phase dimming (incandescent variants)

Color Rendering: Ra \geq 90 for LED variants.


Performance dependent upon screw-base lamp used in socketed variants.




Related products




VL 45 Radiohus Pendant




VL Ring Crown 3-5-7 Pendant




VL Ring Crown 1 Pendant




VL Ring Crown 2 Wall Lamp



VL Studio Table/Floor Lamp



VL Studio Wall Lamp



Product variants

Dimension	Color	Light source	Lumen	Voltage frequency	Class	Lighting control	
VL 45 Radiohus Pale Rose Pendant	<ul style="list-style-type: none"> ● Brass/glossy amber glass ● Brass/glossy pale rose glass ● Brass/glossy pale yellow glass ○ Brass/glossy white opal glass 	VL Ring Crown 1 Wall Lamp	VL 45 Radiohus Portable Lamp	-	-	-	-
6.9"		1x100W E27	2763	120V	I	Dim 0-10v	
9.8"		1x10W E12	3353			Phase dimming (mains dimm)	
		1x10W G16.5/candelabra					
		1x20W E14					
		1x22W A-21/medium					
		LED 3000-1800K D2W 44W					
		LED 3000K 44W					

Design

Vilhelm Lauritzen

Weight

Min: 1.312 lbs Max: 8.971 lbs

Dimensions

14.6", 6.9", 9.8"

Finish

Brass/glossy amber glass, Brass/glossy pale rose glass, Brass/glossy pale yellow glass, Brass/glossy white opal glass

Voltage

120V

Spare parts & accessories

Product	Variant number
VL 45 Radiohus Ø250 White Opal glass	5741099304
VL 45 Radiohus Ø370 White Opal glass	5741099317
VL 45 Radiohus LED Ø370 White Opal glass	5741100866
VL 45 Radiohus Ø370 suspension	5741928543
VL 45 Radiohus Ø250 White Opal glass	5741105829
VL 45 Radiohus Ø175 suspension	5741940932